LUUM

Flexagon

Name Flexagon

Designer Suzanne Tick

Style No. 4026

Use Upholstery

Content 50% Solution Dyed Recycled Nylon + 50% Solution Dyed Nylon


Abrasion Wyzenbeek

100,000 double rubs


Special Characteristics Bleach Cleanable

Environmental PFOA/PFOS Free Stain Repellent Recycled Content






Northern Lights 4026-11





Benchmark 4026-03

Compass 4026-02



Field 4026-05



Blueprint 4026-06

Peatlands 4026-10

Core 4026-04



Isobar 4026-12



Night Vision 4026-09



Flame Retardancy

Maintenance

Environmental

Origin

Flexagon 4026

Suzanne Tick

Use: Upholstery Weight: 11.8 ± 0.1 oz per linear yard **Width:** 54" Directional: Yes

Acrylic Backing Stain Repellent

Seam Slippage: ASTM D4034 Warp 81 lbf, Fill 83 lbf Colorfastness to Light: AATCC 16, Grade 5 at 40 Hours Pilling: ASTM D3511 (Brush Pill), Class 5

Cal TB 117-2013, UFAC Class 1, NFPA 260

WS, Clean with either a water-based or solvent-based cleaning agent. Bleach Cleanable: 20% (4:1 Ratio), wipe with water after solution.

PFOA/PFOS Free Stain Repellent **Recycled** Content

Canada

Dye lots may vary slightly from samples shown. Samples shown off the bolt.



Canada 877.705.LUUM luumtextiles.ca

cdn/us/int/05-16

© Teknion 2016. [®],™ Trademarks of Teknion Corporation and/or its subsidiaries or licensed to it. *Certification Marks owned by the Association for Contract Textiles, Inc.





Content: 50% Solution Dyed Recycled Nylon (Preconsumer) + 50% Solution Dyed Nylon

Pattern Repeat: Horizontal 7.28" Vertical 3.87" Random Match

Abrasion: ASTM D4157 Wyzenbeek 100,000 double rubs Breaking Strength: ASTM D5034 Warp 354 lbf, Fill 361 lbf Colorfastness to Crocking: AATCC 8, Wet Class 4.5, Dry Class 4.5

USA 877.705.LUUM luumtextiles.com

International 919.464.2922 luumtextiles.com