

teknion boulevard

Grade 1 Fabrics

Anchorage	2
Aurora	4
Chance	5
Linea	6
Loopy	7
Melody	8
Merge	9
Pinpoint	10
Streak	11
Tek	12
Terrace	13

Grade 2 Fabrics

Cyclone	14
Dashing	15
Quadrille	16

Click each fabric name in this contents page for more information.

teknion boulevard


Anchorage | Grade 1



Birch
AN40




Green Apple
AN41



Lapis
AN42



Straw
AN43



Wolf
AN44




Goose
AN45



Angora
AN46




Cumin
AN47



Asteroid
AN48




Geranium
AN49




Thistle
AN50



Graphite
AN51



Slate
AN52



Quarry Blue
AN53



Onyx
AN54




Pumpkin
AN55


Content	Width	Cleaning Code	Weight	Flammability Test & Result
35% Post-Consumer Recycled Polyester / 65% Pre-Consumer Recycled Polyester	66 in min. useable / 168 cm	Water & Solvents	15.0 oz / LY	ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes

teknion boulevard


Anchorage | Grade 1




Red Delicious
AN56



Sunshine
AN57




Vanilla
AN61




Cobalt
AN62

Content	Width	Cleaning Code	Weight	Flammability Test & Result
35% Post-Consumer Recycled Polyester / 65% Pre-Consumer Recycled Polyester	66 in min. useable / 168 cm	Water & Solvents	15.0 oz / LY	ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes




Cloud
AU20



Seal
AU21



Fog
AU22



Pewter
AU23



Granite
AU24



Oat
AU25



Coconut
AU26



Latte
AU27



Lake
AU28




Frost
AU29


Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Polyester / 80% minimum Post-Consumer Recycled Polyester	66 in / 168 cm	Water & Solvents	12.94 oz / LY	AATCC-16A - Class 4.5	CAL TB117-2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034 - Warp: 307 lbs / Fill: 210 lbs

teknion boulevard


Chance | Grade 1




Mist
CN51




Dill
CN52




Island
CN53



Plaza
CN54




Tranquil
CN55



Navajo
CN57



Prairie
CN58




Cinder
CN59




Oasis
CN66


Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
63% Virgin Polyester / 37% Post-Consumer Recycled Polyester	66 in / 168 cm	Water & Solvents	10.8 oz / LY	AATCC-16A - Class 4.5	CAL TB117-2013 - Passes	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 275 lb / Fill: 200 lb	ASTM D4034 - Warp: 104 lb / Fill: 77 lb




Queue
LN41




Cord
LN42




Twine
LN43




Thread
LN44




Contour
LN45



Silhouette
LN46



Cable
LN47



Route
LN48

Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
100% Post-Consumer Recycled Polyester	67 in / 168 cm	Water & Solvents	11 oz / LY	AATCC-16A - Class 5	ASTM E84 - Class 1 or A	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb	ASTM D4034 - Warp: 104 lb / Fill: 77 lb

teknion boulevard

Loopy | Grade 1



Oyster
LP60




Putty
LP61




Marble
LP62



Hazelnut
LP63




Latte
LP64



Bay
LP65



Wild Rice
LP66



Harbor
LP67

Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Post-Industrial Polyester	66 in	Water & Solvents	10.4 +/- 0.3 oz / LY	California Technical Bulletin 117 /Section E - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 3.5	ASTM D5034-95 - Warp: 266 lb / Fill: 203 lb

teknion boulevard

Melody | Grade 1



Spray
ME40



Pond
ME41



Sand Bar
ME42



Silt
ME43



Pebble
ME44



Lake
ME45



Gravel
ME46



Boulder
ME47

Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Recycled Polyester	66 in / 168 cm	Water & Solvents	11.6 +/- 0.5 oz / LY	AATCC-16A - Class 4	California Technical Bulletin 117 /Section E - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 3.5	ASTM D5034-95 - Warp: 225 lb / Fill: 100 lb

teknion boulevard

Merge | Grade 1



Fawn
MG20



Marshmallow
MG21



Driftwood
MG22



Dove
MG23




Graphite
MG24




Slate
MG25



Eucalyptus
MG26



Fire Engine
MG27




Mediterranean
MG28




Midnight
MG29


Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Polyester / 75% minimum Post-Consumer Recycled Polyester	66 in / 168 cm	Water & Solvents	16.2 oz / LY	AATCC-16A - Class 4.5	CAL TB117-2013 - Passes / ASTM E-84 - Class A	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034 - Warp: 325 lbs / Fill: 275 lbs




Bliss
PN11




Delight
PN12




Dune
PN13




Infusion
PN14




Ebony
PN15




Fresh
PN16




Carrot
PN17



Splash
PN18



Vibe
PN19



Gala
PN20

Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
100% Post-Consumer Recycled Polyester	67 in / 168 cm	Water & Solvents	11 oz / LY	AATCC-16A - Class 5	ASTM E84 - Class A	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb	ASTM D4034 - Warp: 104 lb / Fill: 77 lb

teknion boulevard

Streak | Grade 1



Beach
SR81




Shade
SR86



Stretch
SR88




Sprint
SR89



Roll
SR91



Dart
SR92




Zoom
SR93



Splash
SR94



Whiz
SR95




Flash
SR96

Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Post-Consumer Recycled Polyester	66 in	Water & Solvents	11 oz / LY	ASTM E84 - Class A / Class 1	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb

teknion boulevard

Tek | Grade 1




Finesse
TX60



Grain
TX61



Essence
TX62




Warp
TX64




Mesh
TX67



Form
TX69



Spice
TX71




Glacier
TX72




Spring
TX73



Harmony
TX74




Smoke
TX75




Pebble
TX76

Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Post-Consumer Recycled Polyester	67 in	Water & Solvents	11 oz / LY	ASTM E84 - Class A / Class 1	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb


Terrace | Grade 1




Lotus
TC60




Tigerlily
TC61




Shadow
TC62




Cobble
TC63



Cherry Blossom
TC64



Bluebell
TC65



Apple
TC66




Haze
TC67




Cerise
TC68



Twilight
TC69



Wintergreen
TC70




Ironwork
TC71




Pine Cone
TC72



Flirt
TC73




Echo
TC74




Glacier
TC75


Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
70% Virgin Polyester / 30% Post-Consumer Recycled Polyester	48 in	Water & Solvents	10.54 oz / LY	CAL TB117- 2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 3	ASTM D5034-95 - Warp: 279 lb / Fill: 211 lb	ASTM D4034 - Warp: 140.6 lb / Fill: 68.6 lb




Wrought Iron
IM36




Stove Pipe
IM37



Stainless
IM40




Polished Pewter
IM41



Welded Steel
IM43




Etched Bronze
IM44




Fired Titanium
IM46




Chrome
IM49



Dark Annealed
IM50




Karat
IM54




Red Metal
IM55




Oxidized Bronze
IM56



Bright Ray
IM57



Bismuth Crystal
IM58



Gallium Blue
IM59

Content	Width	Cleaning Code	Weight	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Polyester	66 in / 168 cm	Water & Solvents	15.5 oz / LY	AATCC-16A - Class 5	ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034-95 - Warp: 190 lb / Fill: 150 lb

Dashing | Grade 2



Classic Silver
DS21



Refined Marble
DS22



Antique Sage
DS23



Polished Slate
DS24



Genteel Beige
DS25




Bespoke Tan
DS26



Dapper Grey
DS27

Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result
100% Eco Intelligent Polyester	66 in	Water & Solvents	10.9 oz / LY	CAL TB117-2013 - Class 5	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 240.6 lb / Fill: 191.3 lb


Quadrille | Grade 2



Escapade
QU30



Shenanigan
QU31



Revelry
QU32




Spring
QU33



Regalia
QU34



Soiree
QU35



Zest
QU36



Gambol
QU37




Leisure
QU38



Fair
QU39




Fiesta
QU40




Carnival
QU41

Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
52.5% Polyester / 47.5% Recycled Polyester	48 in	Water & Solvents	12.11 oz / LY	CAL TB117- 2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034-95 - Warp: 249.5 lb / Fill: 271.5 lb	ASTM 3597 D434-95 - Warp: 73.02 lb / Fill: 91.35 lb

Quadrille | Grade 2



Spree
QU42




Opus
QU43



Jubilee
QU44



Masquerade
QU45



Cabaret
QU46

Content	Width	Cleaning Code	Weight	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
52.5% Polyester / 47.5% Recycled Polyester	48 in	Water & Solvents	12.11 oz / LY	CAL TB117- 2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034-95 - Warp: 249.5 lb / Fill: 271.5 lb	ASTM 3597 D434-95 - Warp: 73.02 lb / Fill: 91.35 lb

teknion boulevard

COLORWAY	Content	Width	Cleaning Code	Weight	Abrasion	Colorfastness to Light Test & Result	Flammability Test & Result	Crocking Test & Result	Breaking Strength Test & Result	Seam Slippage
ANCHORAGE	35% Post-Consumer Recycled Polyester / 65% Pre-Consumer Recycled Polyester	66 in min. usable / 168 cm	Water & Solvents	15.0 oz / LY			ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes			
AURORA	100% Polyester / 80% minimum Post-Consumer Recycled Polyester	66 in / 168 cm	Water & Solvents	12.94 oz / LY		AATCC-16A - Class 4.5	CAL TB117-2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034 - Warp: 307 lbs / Fill: 210 lbs	
CHANCE	63% Virgin Polyester / 37% Post-Consumer Recycled Polyester	66 in / 168 cm	Water & Solvents	10.8 oz / LY		AATCC-16A - Class 4.5	CAL TB117-2013 - Passes	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 275 lb / Fill: 200 lb	ASTM D4034 - Warp: 104 lb / Fill: 77 lb
LINEA	100% Post-Consumer Recycled Polyester	67 in / 168 cm	Water & Solvents	11 oz / LY		AATCC-16A - Class 5	ASTM E84 - Class 1 or A	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb	ASTM D4034 - Warp: 104 lb / Fill: 77 lb
LOOPY	100% Post-Industrial Polyester	66 in	Water & Solvents	10.4 +/- 0.3 oz / LY			California Technical Bulletin 117 / Section E - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 3.5	ASTM D5034-95 - Warp: 266 lb / Fill: 203 lb	
MELODY	100% Recycled Polyester	66 in / 168 cm	Water & Solvents	11.6 +/- 0.5 oz / LY		AATCC-16A - Class 4	California Technical Bulletin 117 / Section E - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 3.5	ASTM D5034-95 - Warp: 225 lb / Fill: 100 lb	
MERGE	100% Polyester / 75% minimum Post-Consumer Recycled Polyester	66 in / 168 cm	Water & Solvents	16.2 oz / LY		AATCC-16A - Class 4.5	CAL TB117-2013 - Passes / ASTM E-84 - Class A	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034 - Warp: 325 lbs / Fill: 275 lbs	
PINPOINT	100% Post-Consumer Recycled Polyester	67 in / 168 cm	Water & Solvents	11 oz / LY		AATCC-16A - Class 5	ASTM E84 - Class A	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb	ASTM D4034 - Warp: 104 lb / Fill: 77 lb
STREAK	100% Post-Consumer Recycled Polyester	66 in	Water & Solvents	11 oz / LY			ASTM E84 - Class A / Class 1	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb	
TEK	100% Post-Consumer Recycled Polyester	67 in	Water & Solvents	11 oz / LY			ASTM E84 - Class A / Class 1	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 100 lb / Fill: 100 lb	
TERRACE	70% Virgin Polyester / 30% Post-Consumer Recycled Polyester	48 in	Water & Solvents	10.54 oz / LY			CAL TB117-2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 3	ASTM D5034-95 - Warp: 279 lb / Fill: 211 lb	ASTM D4034 - Warp: 140.6 lb / Fill: 68.6 lb
CYCLONE	100% Polyester	66 in / 168 cm	Water & Solvents	15.5 oz / LY		AATCC-16A - Class 5	ASTM E-84 - Passes California Technical Bulletin 117 / Section E - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034-95 - Warp: 190 lb / Fill: 150 lb	
DASHING	100% Eco Intelligent Polyester	66 in	Water & Solvents	10.9 oz / LY			CAL TB117-2013 - Class 5	(Dry) AATCC-8 - Class 5 (Wet) AATCC-8 - Class 5	ASTM D5034-95 - Warp: 240.6 lb / Fill: 191.3 lb	
QUADRILLE	52.5% Polyester / 47.5% Recycled Polyester	48 in	Water & Solvents	12.11 oz / LY			CAL TB117-2013 - Passes	(Dry) AATCC-8 - Class 4 (Wet) AATCC-8 - Class 4	ASTM D5034-95 - Warp: 249.5 lb / Fill: 271.5 lb	ASTM 3597 D434-95 - Warp: 73.02 lb / Fill: 91.35 lb