## LUUM

| Direct Glue Wallcovering<br>Installation Guidelines | Please inspect installation after three drops of the fabric. If there are any issues, please stop<br>installation and inform your Luum Textiles representative or customer service at 1-877-705-LUUM<br>(1-877-705-5886). Luum Textiles cannot accept any claims on labor or material of more than three<br>lengths (9 linear yards or 8.2 metres) that have been cut and installed.   |
|---|--|
| Inspection  | Confirm all rolls are the correct pattern and color.   |
| Storage   | <ul> <li>Be sure to store fabric in a clean, dry environment.</li> <li>Do not store rolls standing on end.</li> </ul>  |
| Wall/Space Preparation                              | <ul> <li>Wall surfaces must be completely smooth, clean and dry.</li> <li>Use a high quality white wall primer on all wall surfaces prior to installation. Walls must be a uniform color.</li> <li>Finished lighting must be in place before hanging fabric.</li> </ul>  |
| Cutting   | <ul> <li>Cut at least 2-3" (5-8 cm) from each selvedge with a straight-edge and sharp knife blade. A new blade is recommended for each cut.</li> <li>Mark "Top" at the time of cutting on each strip. (Note: on light colored fabrics, be sure to use a method that won't telegraph through to the face, avoiding too much pencil or ink.)</li> <li>Fabric can be table cut or doublecut on the wall at the discretion of the hanger.</li> </ul> |
| Adhesive  | <ul> <li>Use a high quality, heavy-duty, clear, vinyl adhesive.</li> <li>Do not dilute the adhesive.</li> <li>Avoid getting any adhesive on the face of the fabric, but if it does happen allow it to dry and clean with a dry brush or follow adhesive manufacturer's instructions.</li> </ul>  |
| Wall Application                                    | <ul> <li>Apply adhesive to the wall (not the back of the fabric) and allow it to become tacky.</li> <li>Do not reverse hang panels.</li> <li>Hang panels in order they came off bolt.</li> <li>Do not stretch fabric or overwork the seams.</li> <li>When cornering, apply at least 6" (15 cm) around the corner.</li> </ul>   |

**Canada** 877.705.LUUM luumtextiles.ca **USA** 877.705.LUUM luumtextiles.com International 919.464.2922 luumtextiles.com

Visit the Luum website for additional information including warranty, terms & conditions and ordering information. For textiles inquiries, please contact Luum customer service.