LUUM Datatown

Name

Datatown

Designer

Suzanne Tick

Style No.

7009

Use

Direct Glue Wall

Content

100% Recycled Polyester

Environmental

Recycled Content



ARRECTATION OF THE CAME OF THE PARTIES OF THE PARTI utbulnisenso in tous situs sun sun ton ton telle in in the destruction in the second situs situs sun ton ton t Here in the second situs is the second situs in the destruction in the second situs in the second situs in the The transfer of the state and the state of t ede la dissiplication adjustica din simux di collistatores de la dissiplication adjustica din simux La colonia la colonia de l transportation and the state of katharan inggarar na ang kamang ang kang ang kang ang ang ang kataran na kang na ang katarang ang kang kang ka Every and design of the property of the proper ingrafe ter ann gaglion secret tarben schalle betatt betat tarbente for ann gaglion secret tarbente and And the state of t 110-PAISSELAN MOTANGENIAN PANET SEPANTAL PANET SELATAPAN PANET SENIAN PANET SENIAN PANET PANET SE gelagraaanenalisekariseaariseakistassapaari-arenariabiaaaaaneriabiahariseakista artubialisaetaetan matuliaaseg mastabatubiabatubiah eta katabatabatan matuliabatubia. Maturi bear matubiabiah eta mila matubiah atabatabatabat matubia matubiabiah matubiabatabatabatabatabatabataba Teledition of the control of the con n Cost na Lagran Audurnat ann na Gan Lagran Lagra ann Tabrana na Cost na Lagran Addinat ann an Gan Lagranga an

Ping 7009-01


Binary 7009-02



Gigabyte 7009-05




Upload 7009-03



Virtual 7009-06



Utility 7009-04



Browser 7009-07

Name — Datatown

Style No. — 7009

Designer Suzanne Tick

Specification Use: Direct Glue Wall

Content: 100% Recycled Polyester (54% Preconsumer, 46% Postconsumer)

Weight: 15.7 ± 1.0 oz per linear yard

Width: 54"

Pattern Repeat: None Directional: Yes

Finish Acrylic Backing Stain Repellent

Performance

Breaking Strength: ASTM D5034 Warp 275 lbf, Fill 136 lbf **Colorfastness to Light:** AATCC 16, Grade 5 at 40 Hours **Colorfastness to Crocking:** AATCC 8, Wet Class 5, Dry Class 5

Flame Retardancy ASTM E84 Adhered Class A or 1

Maintenance WS, Clean with either a water-based or solvent-based cleaning agent.

Environmental Facts 3rd-party certified to NSF/ANSI 336 Silver

Recycled Content

Origin USA

Dye lots may vary slightly from samples shown. Samples shown off the bolt.

🍎 * 🛊 🌀 facts **

Canada 877.705.LUUM luumtextiles.ca

JUUM 877.705.LUUM es.ca luumtextiles.com

International 919.464.2922 luumtextiles.com

cdn/us/int/05-16

© Teknion 2016.

,™ Trademarks of Teknion Corporation and/or its subsidiaries or licensed to it *Certification Marks owned by the Association for Contract Textiles, Inc.

A2 — SC-305-7009