LUUM **Emit**

Name

Emit

Designer

Suzanne Tick

Style No. 1025

Use

Wrapped Wall Panel

Content

44% Recycled Polyester + 56% Polyester

Special

Characteristics

Bleach Cleanable

Environmental

Heavy Metal Free NSF/ANSI 336 Silver Recycled Content




Surge 1025-05






Joule 1025-03





Dazzle 1025-04



Hertz 1025-02



Particle 1025-06



Watt 1025-01

Emit

1025 Style No.

Designer Suzanne Tick

Use: Wrapped Wall/Panel Specification

Content: 44% Recycled Polyester (29% Preconsumer + 15% Postconsumer)

+ 56% Polyester

Weight: 14.45 oz per linear yard

Width: 66"

Pattern Repeat: Horizontal 5.38" Vertical 0.13"

Directional: Yes

Finish Acrylic Backing

Breaking Strength: ASTM D5034 Warp 195 lbf, Fill 250 lbf Performance

Colorfastness to Light: AATCC 16, Grade 4 at 40 Hours Colorfastness to Crocking: AATCC 8, Wet Class 3, Dry Class 4

Flame Retardancy ASTM E84 Unadhered Class A

Maintenance WS, Clean with either a water-based or solvent-based cleaning agent.

Bleach Cleanable: 9% (10:1 Ratio), wipe with water after solution.

Heavy Metal Free **Environmental**

NSF/ANSI 336 Silver (1st party certified)

Recycled Content

Origin USA

Dye lots may vary slightly from samples shown. Samples shown off the bolt.

W ** ** **

Canada 877.705.LUUM <u>luumtextiles.ca</u>

877.705.LUUM luumtextiles.com

International 919.464.2922 $\underline{luumtextiles.com}$

cdn/us/int/10-16

© Teknion 2016.

"." Trademarks of Teknion Corporation and/or its subsidiaries or licensed to it.
"Certification Marks owned by the Association for Contract Textiles, Inc.

A2-P1 - SC-305-1025